

Gas Leak Detector

HT601A/B HT601A+/B+



HT601A



HT601B

Specifications	HT601A	HT601A+	HT601B	HT601B+
<b>Range</b>	0~9999ppm / 0.00~20.00%LEL	0~9999ppm / 0.00~20.00%LEL	0~9999ppm / 0.00~20.00%LEL	0~9999ppm / 0.00~20.00%LEL
<b>Detecting gas</b>	combustible gas	combustible gas	combustible gas	combustible gas
<b>Accuracy</b>			≤10% FS(methane)	≤10% FS(methane)
<b>Sensitivity</b>	<50ppm(methane)	<50ppm(methane)	<50ppm(methane)	<50ppm(methane)
<b>Response Time</b>	<2 sec	<2 sec	<2 sec	<2 sec
<b>Warm-Up Time</b>	Approx. 30 sec	Approx. 30 sec	Approx. 30 sec	Approx. 30 sec
<b>Feature</b>				
Display	bargraph	Digit with bargraph	bargraph	Digit with bargraph
Alarm mode	Visible, audible	Visible, audible	Visible, audible	Visible, audible
Auto/Manual Zero	Auto Zero	Auto or Manual Zero	Auto Zero	Auto or Manual Zero
Auto Power Off	✓	✓	✓	✓
Low battery indication	✓	✓	✓	✓
flexible probe	Approx. 16"inch	Approx. 16"inch	Approx. 16"inch	Approx. 16"inch
<b>General</b>				
Power	3x1.5AAA batteries	3.7V Li-ion battery	3x1.5AAA batteries	3.7V Li-ion battery
IN PUT		DC 5V=1A		DC 5V=1A
Weight	Approx. 231g			
Size	225mmX60mmX33mm			